

STATUS 100% ACRYLIC **ACRYLIC COLOUR**

DESCRIPTION

The **STATUS 100% ACRYLIC** is a high quality acrylic paint for exterior use. Offers high water-repellency and excellent resistance to adverse atmospheric conditions and UV radiation over time. It has strong adhesion to all kinds of old and new surface such as plaster, concrete, plaster, wood,

etc. It is odorless, dries quickly and is quite friendly for the user and the environment. Its special formulation provides excellent breathability, high whiteness and resistance to frequent washing. Easy to apply, has excellent hiding power and high efficiency. It gives a beautiful matte finish.

APPLICATION

- Suitable for external application of new or old painted stonework.
- Applied on concrete, plaster, plasterboard, wood, etc.

ADVANTAGES - FEATURES

- Product environmentally friendly solvent-free.
- Odorless
- Does not contain ammonia.
- High water-repellency.
- Excellent breathability of surfaces.
- Excellent resistance to sunlight.
- High resistance to adverse atmospheric Conditions.
- Resistant to washing.
- Fast drying
- Excellent coverage.
- High whiteness
- Excellent workability
- High performance

SUBSTRATE PREPARATION

The surface must necessarily be clean, dry, sound and free from dust, mold, grease before applying. Remove all frayed, or peeling old paint. Where necessary grouting, use the **STATUS 100% ACRYLIC PUTTY** and after drying, rub with sandpaper and dust well. Where there are large cracks, use putty for the ready to use Lightweight, White Stucco **STATUS ONE COVER**, with a single pass without rubbing. On new surfaces, paint a first hand **STATUS ACRYLIC PRIMERS**, or **STATUS DUR WATER**. If

it is fresh plaster or cement, let it dry absolutely thoroughly for at least one month before painting. On gypsum boards or for repainting water painted surfaces (with lime or glue) or soiled surfaces (nicotine, soot from heaters, soot, fumes, coffee, juice, graffiti, inks, markers, mildew, mold, moisture, oil, etc.), prime first with **STATUS DUR**. Do not ever paint surfaces that may contain moisture. First make sure that the cause of the moisture stopped and that the surface is completely dry.

APPLICATION

Stir well the contents of the container before use, dilute properly and apply 1-2 coats of paint. Apply the second layer at least 2-3 hours after the first. After use close well the container to maintain in good condition for future use. It can be stored in a tightly closed container, without any problem for a long period provided that it hasn't been diluted with water. The painted surfaces is recommended not to be washed until

20-30 days have passed after the paint application. On newly plastered or concreted surfaces the paint application can be done only after 30-40 days. **STATUS** bases are used exclusively for the production of shades through the **STATUS** tinting system and should not be applied without the addition of special **STATUS** pigments. Very dark colors in matte shades that are subject to frequent washing are not recommended.

Technical Support Line 800 100 14 14 info@thrakon.gr • www.thrakon.gr

DRYING

Dries in 1-2 hours, so as not to leave stains on touch. Full resistance to washing after 4 weeks.

RECOATABILITY

Recoated after 2-3 hours, Drying times refer to normal ambient conditions (25 ° C, 60% humidity). Any differences in temperature and humidity of the environment can alter the above times.

COLOURS

Available in white and thousand more shades through the STATUS tinting system.

CONSUMPTION

10-12 m² / lt, depending on the texture and porosity of the surface.

TOOLS APPLICATION

Brush, roller, or airless spray gun.

CLEANING TOOL

Immediately after use, drain thoroughly the paint inside the container and clean all tools with hot water and soap. Do not empty washings into the groundwater.

PACKAGING

Available in plastic containers of 0,75 lt, 3 lt, 10 lt.

STORAGE

In the original, sealed packaging in dry environment at temperatures between +5 ° C and +35 ° C for 12 months from date of production.

VOLATILE ORGANIC COMPOUNDS (VOC)

- Maximum allowable VOC content (Directive 2004/42/EC) for the product category A / c 'Coatings & exterior walls of mineral substrate, type Y, PHASE II: 40 gr / lt

- Maximum VOC content of the product ready for use: 35 gr / lt

APPLICATION TEMPERATURE

Do not paint in temperatures below 10 ° C or before rain. In applying the surface should not come in direct exposure to solar

radiation. Adverse conditions during or immediately after application may affect the final properties of the product.

The technical information and instructions in this brochure relating to the application and end-use of products based on Thrakon up this expertise and experience of the products and are given in good faith when properly stored, handled and applied in accordance with the instructions of Thrakon. Due to the inability to directly inspect the conditions at the construction site and the implementation process of the product, the Company makes no guarantee regarding the suitability of its products for any particular purpose and disclaims any legal responsibility which is based on quoted information in this booklet, written or oral or otherwise provided recommendations and instructions. Users are advised to perform a little test on the product's suitability for the intended application and purpose. Thrakon reserves the right to change the properties of its products without prior notice. All orders are accepted only after the acceptance of the above and under the current terms of trade policy of the Company. The edition of this technical datasheet automatically cancels any previous one.

STATUS 100% ACRYLIC ACRYLIC COLOR



PRECAUTIONS

For information on the safe use, storage and disposal of the product read the information on the label and in the most recent MSDS of the product before the product MSDS is available upon request to the professionals. The leftover

colors should not be disposed of with household waste. You should seek advice from local authorities on the disposal and collection of waste.

Poisons Information Centre Tel. 210 77.93.777

TECHNICAL CHARACTERISTICS	UNITS	STANDARD	PRICE
Density (20°C)	White and bases (g/ml)	EN ISO 2811.01-02	1,42 ± 0,05
Viscosity	(cps)	Brookfield	10.000-20.000
pH		ISO 976-96	8-8,7
Gloss (65°)	(mm)	EN ISO 2813-99	< 7
Accelerated aging by UV radiation (2000h)	(°C)	ISO 11507-97	There is no alteration of the film
Dilute with water	(% κ.ο.)	-	5-10

Note: Measurements are done in a laboratory environment temperature +230 C, RH 50%, and without aeration. There is the possibility to vary depending on the conditions at the site such as temperature, humidity, ventilation and absorbency of the substrate.