

STATUS ECO ECO EMULSION PAINT



DESCRIPTION

STATUS PLASTIC is a high quality emulsion paint ideal for indoors. It is odourless and completely friendly for the user and the environment. It is easy to apply, it

spreads superbly and it has excellent hiding power and high efficiency. The result is a rich matte surface, resistant to washing, maintaining the beautiful appearance for very long.

AREAS OF APPLICATION

- Suitable for interiors on all common surfaces such as walls, plaster, ceilings, plasterboards, spatula coated surfaces, etc.
- Use on wooden surfaces after adequate preparation.

ADVANTAGES - SPECIFICATIONS

- Environment-friendly and solvent-free. It has ECO labeling.
- Odorless
- Does not contain ammonia.
- Excellent breathability of surfaces.
- Excellent resistance to sunlight.
- Resistant to washing.
- Excellent coverage.
- High resistance to weathering and aging
- Suitable for painting nurseries, children's rooms, schools, hospitals.
- Excellent workability

SUBSTRATE PREPARATION

Before use, ensure that the surface is clean, dry, robust and free from dust, mold and grease. Remove damaged, or peeling old paint. Where puttying is required, use the Status 100% Acrylic Stucco and after drying, sand the surface down and dust well. If there are large cracks,

use ready-to-use light white Stucco, **STATUS ONE COVER**, to fill the cracks applying just one coat without sanding.

On new surfaces, first apply one coat of **STATUS ACRYLIC PRIMER**, or **WATER-BASED STATUS DUR**. For surfaces covered in fresh plaster or cement, allow the surfaces to dry thoroughly for at least 1 month before painting.

APPLICATION

Mix well before use, dilute properly and apply 1-2 coats of paint. Allow at least 2-3 hours before applying the second coat. Close the container tightly after use to keep the paint in good condition for future use. You can store undiluted paint in a tightly sealed container for extended periods of time without affecting the quality of the product. Allow 20-30 days before washing freshly

Painted surfaces and 30-40 days before washing freshly painted new plaster or concrete surfaces.

STATUS ECO bases are used solely with the STATUS painting system to create the various color shades and should not be used as is without adding the special **STATUS** colorants. The use of very dark colors in matte paints that are subject to frequently washing is not recommended.

DRYING

Dries out after 1-2 hours, so as not to leave stains on touch. Full resistance to washing after 4 weeks.

RECOATABILITY

Recoated after 2-3 hours, Drying times refer to normal ambient conditions (25 ° C, 60% humidity). Any differences in temperature and humidity of the environment can alter the above times.

COLOURS

Available in white and thousand more shades through the STATUS tinting system.

CONSUMPTION

12-15 m² / lt, depending on the texture and porosity of the surface.

TOOLS APPLICATION

Brush, roller, or airless spray gun.

CLEANING TOOL

Immediately after use, drain thoroughly the paint inside the container and clean all tools with hot water and soap. Do not empty washings into the groundwater.

PACKAGING

Available in plastic containers of 0,75 lt, 3 lt, 10 lt.

STORAGE

In the original sealed packaging in dry environment at temperatures between +5 ° C and +35 ° C for 12 months from date of production.

VOLATILE ORGANIC COMPOUNDS (VOC)

- Maximum VOC content limit values (Directive 2004/42/CE) for this product category A/a "Interior matt walls and ceilings (Gloss 25@60°)", Type WB, PHASE II: 15 g/l
- Maximum VOC of product ready to use: 13 g/l

NOTES

More information about the reasons why this product has been awarded with the Eco-label is available in the website of EC:

<http://ec.europa.eu/environment/ecolabel/>

APPLICATION TEMPERATURE

Do not paint in temperatures below 10 ° C or before rain. During application surface should not come in direct exposure to solar radiation. Adverse conditions during

or immediately after application may affect the final properties of the product.

STATUS ECO ECO EMULSION PAINT



PRECAUTIONS

For information on the safe use, storage and disposal of the product read the information on the label and in the most recent MSDS. MSDS is available upon request to the professionals. The paint leftovers should not be disposed

with household waste. You should seek advice from local authorities on the disposal and collection of waste.
Poisons Information Centre Tel. 210 77.93.777

TECHNICAL CHARACTERISTICS	ΜΟΝΑΔΕΣ	ΠΡΟΤΥΠΟ	ΤΙΜΗ	
Density (20°C)	(g/ml)	EN ISO 2811.01-02	White and bases P,D	1,45 ± 0,05
			Base TR	1,32 ± 0,05
Viscosity	(cps)	Brookfield	10.000-20.000	
pH		ISO 976-96	8-8,7	
Gloss (60°)		EN ISO 2813-99	< 4	
Resistance to washing-scrubbing	(Class)	EN ISO 11998-02	1	
Exposure to fluorescent UV and water	(°C)	ISO 11507-97	There is no visible change of the film	
Dilute with water	(% v/v)	-	5-10	

Σημείωση: Οι μετρήσεις έχουν γίνει σε εργαστηριακό περιβάλλον θερμοκρασίας +23°C, Σ.Υ. 50% και χωρίς αερισμό. Υπάρχει η πιθανότητα να διαφέρουν ανάλογα με τις συνθήκες που επικρατούν στο εργοτάξιο όπως θερμοκρασία, υγρασία, αερισμός και απορροφητικότητα του υποστρώματος.